



touching tomorrow, today

8F., No.445, Sec. 2, Zhongbei Rd., Zhongli City, Taoyuan County 32087, Taiwan (R.O.C.)

TEL: +886-3-456-6101 FAX: +886-3-456-6102

32087桃園縣中壢市中北路二段445號8F

電話：+886-3-456-6101 傳真：+886-3-456-6102

訂單位 Department	文件名稱 Subject	文件編號 Document No.	
產品企劃部 Product Planning Dept.	產品規格書 Product Specifications	總頁數 Total Page	Page 1 / 15

Projected Capacitive Touch Panel Product Specification

對象客戶 Customer	
產品簡述 Product Description	15.6 INCH PROJECTED CAPACITIVE TOUCH PANEL
規格書適用級別 Application Level	<input type="checkbox"/> Preliminary Reference Only. <input checked="" type="checkbox"/> Sample Used Only. <input type="checkbox"/> Mass-Production Used.
申請日期 Apply Date	2017-07-31
規格書版次別 Spec. Version	1.0
產品型號 Part Number	MT9D156C55125
客戶確認 Approved By Customer	
客戶料號 Customer Part No.	
審核人員 Checked By	
核准人員 Approved By	

核准窗口 Approved By	審核窗口 Checked By	制定窗口 Prepared By
Jeffrey Chou	Alex Lin /Milton Hong	Lance Lu



touching tomorrow, today

8F., No.445, Sec. 2, Zhongbei Rd., Zhongli City, Taoyuan
County 32087, Taiwan (R.O.C.)

TEL: +886-3-456-6101 FAX: +886-3-456-6102

32087桃園縣中壢市中北路二段445號8F

電話：+886-3-456-6101 傳真：+886-3-456-6102

訂單位 Department	文件名稱 Subject	文件編號 Document No.	
產品企劃部 Product Planning Dept.	產品規格書 Product Specifications	總頁數 Total Page	Page 2 / 15

目 錄

TABLE OF CONTENTS

0. 修正履歷 REVISION HISTORY -----	03
1. 一般說明 GENERAL DESCRIPTION -----	04
1.1 產品概要 OVERVIEW	
1.2 產品特徵 FEATURES	
1.3 通用規格 GENERAL SPECIFICATIONS	
1.4 觸控面板規格 TOUCH PANEL SPECIFICATIONS	
2. 可靠度測試報告與規範 RELIABILITY TEST REPORT AND SPECIFICATIONS -----	06
2.1 機械特性 MECHANICAL CHARACTERISTICS	
2.2 可靠度規格 RELIABILITY SPECIFICATIONS	
3. 外觀檢驗 APPEARANCE AND COSMETIC INSPECTION -----	08
3.1 檢驗環境參數 INSPECTION ENVIRONMENT CONDITIONS	
3.2 目視檢驗規範 COSMETIC SPECIFICATIONS	
4. 預防措施 PRECAUTIONS -----	12
5. 標籤釋義 PRODUCT LABEL EXPLANATION -----	13
5.1 條碼定義 BARCODE DEFINITION	
6. 觸控面板圖面 TOUCH PANEL DRAWING -----	15

Confidential



touching tomorrow, today

8F., No.445, Sec. 2, Zhongbei Rd., Zhongli City, Taoyuan

County 32087, Taiwan (R.O.C.)

TEL: +886-3-456-6101 FAX: +886-3-456-6102

32087桃園縣中壢市中北路二段445號8F

電話：+886-3-456-6101 傳真：+886-3-456-6102

訂單位 Department	文件名稱 Subject	文件編號 Document No.	
產品企劃部 Product Planning Dept.	產品規格書 Product Specifications	總頁數 Total Page	Page 3 / 15

修正履歷

REVISION HISTORY

項次 Item	版次 Version	修正日期 Date	摘要敘述 Description	頁數 Page
1	V1.0	2017-07-13	First release.	P.1~P15
2				
3				
4				
5				
6				
7				
8				
9				
10				
11				
12				
13				
14				
15				
16				
17				
18				
19				
20				

訂單位 Department	文件名稱 Subject	文件編號 Document No.	
產品企劃部 Product Planning Dept.	產品規格書 Product Specifications	總頁數 Total Page	Page 4 / 15

1. 一般說明 GENERAL DESCRIPTION

1.1 產品摘要 OVERVIEW

這是一款採用 USB 介面並支援 WIN8 作業系統已達到可以 10 指觸控作業的投射式電容觸控面板。

It is a Projected Capacitive Touch Panel with USB interface to support and compatible with WIN8 O/S system for multi-touch application.

1.2 產品特徵 FEATURES

項次 ITEMS	規格 SPECIFICATIONS
面板尺寸 Panel Size	15.6 inch
產品結構 Structures	Glass/Glass (ITO glass with Chemical enhanced)
總厚度值 Total Thickness	2.4 ± 0.2 mm (Cover_1.1 mm & Sensor_1.1 mm)
作業條件 Operation Conditions	5°C ~ +60°C at Min 20% to Max 90% RH
儲存條件 Storage Conditions	-15°C ~ +65°C at Min 10% to Max 90% RH
靜電防護等級 ElectroStatic Discharge (Non-Operation)	Contact : ±4KV, 3times/1point, 1time/1sec, Total 3points. Air : ±8KV, 3times/1point, 1time/1sec, Total 3points.

備註 1：為確保觸控模組可有效發揮其功能，請務必於作業時將控制器作有效的接地動作。

Note 1 : In order to make a touch panel operate normally, please make sure that the host device is grounded.

備註 2：觸控面板必須藉由雙面膠帶或其他具有黏性之材料將其與 TFT-LCD 模組作組裝貼合作業，並將觸控面板的控制器反折固定於 TFT-LCD 模組的下鐵框或其他系統機構件上並加以接地；當執行抗靜電防護測試時，允收標準為當沒有外在靜電衝擊時，觸控面板不可有功能性與外觀性的失效或損傷；但是當有靜電衝擊時，若觸控面板有跳動等非規則性之功能性變化時，這種現象是被允許與接受的。

Note 2 : The touch panel must be assembled with LCD panel by VHB or other materials, the control board also be fixed on LCM bezel or other mechanical parts of the system and then be grounded; In ESD test, the function and appearance should be available when electrostatic charge. It is acceptable that the display flicker when electrostatic discharge.

備註 3：假設觸控模組沒有被有效的執行接地動作時，觸控面板可能有功能性受損或不穩定等現象發生。

Note 3 : The touch panel may be damaged functionally or unstable if the panel does not be grounded through your system to earth.

備註 4：為確保觸控模組可有效發揮其功能，電源供應器必須符合 IEC 62684 規範。

Note4 : In order to make a touch panel operate normally, power supply or power adapter have to conform to IEC 62684.

訂單位 Department	文件名稱 Subject	文件編號 Document No.	
產品企劃部 Product Planning Dept.	產品規格書 Product Specifications	總頁數 Total Page	Page 5 / 15

1.3 通用規格 GENERAL SPECIFICATIONS

項次 ITEMS	規格 SPECIFICATIONS	備註 NOTE
輸入方式 Input Method	Finger or Cap. Stylus	
精確度 Accuracy	Within 2.5mm each target & 10% Jitter limit on moving	Based on WIN7 definition ppi(Pixel per inch)
解析度 Resolution	25ppi (Min.)	
玻璃穿透率 Transparency	90% ± 2%	By BYK-Gardner at 550nm.
玻璃霧度值 Haze	3% (Maximum)	

備註 1：上表中所列之光學特性數值的量測是採用檢測儀器(BYK-Gardner)在波長 550nm 的條件測得。

Note 1 : The optical characteristics listed as above are measured by BYK-Gardner instrument at 550nm wavelength.

1.4 觸控面板規格 TOUCH PANEL SPECIFICATION

項次 ITEMS	規格 SPECIFICATIONS
Cover Lens 外觀尺寸 Cover Lens O.D.	386.81 mm * 237.12 mm ± 0.20 mm
Sensor Glass 外觀尺寸 Sensor Glass O.D.	364.81 mm * 225.12 mm ± 0.20 mm
Cover Lens 可視區 C/L Visual Area	345.23 mm * 194.54 mm ± 0.30 mm
FPC/COF 厚度值 FPC/COF Thickness	0.3 mm ± 0.05 mm
軟板長度值 Tail Length	X axis → 20.5 mm ± 0.2 mm * 150 mm ± 1.5 mm (Max. dimensions) Y axis → 34.5 mm ± 0.2 mm * 180 mm ± 1.5 mm (Max. dimensions)

備註 1：觸控面板的玻璃四周與兩側均執行 R 角與 C 角的加工，相關加工規格請參閱圖面尺寸規格的標示與定義。

Note 1 : All of the corners and edges of the glass that have chamfer process by CNC machines and all dimensions and tolerances will be defined on the drawing of the touch panel.

訂單位 Department	文件名稱 Subject	文件編號 Document No.	
產品企劃部 Product Planning Dept.	產品規格書 Product Specifications	總頁數 Total Page	Page 6 / 15


2. 可靠度測試報告與規範 RELIABILITY TEST REPORT AND SPECIFICATIONS

2.1 機械特性 MECHANICAL CHARACTERISTICS

項次 ITEMS		測試條件 CONDITIONS	允收條件 PASS CRITERIA
面板部分 Panel	落球測試 Ball Drop Test	227g ± 2g 40cm	No damage at each cycle drop 5points and each point drop 1time only.
	硬度測試 Hardness	Pencil : 7H Pressure : 0.5N/45°	Hardness ≥ 7H
FPC/COF 可靠度測試	剝離測試方向 Direction of peeling off	90°	Strength ≥ 500gf/cm
FPC/COF Reliability	拉力測試速度 Speed of Pulling out	50mm/min	


備註 1：鋼球落下測試示意圖如下附圖所示。

Note 1 : The ball drop test illustration is showed as follow.



備註 2：玻璃硬度測試依循 JIS K-5400 系列標準規範手法；相關測試示意圖如下附圖所示。

Note 2 : The hardness test follows up the JIS K-5400 serials industry standard and the test illustration is showed as below.




備註 3：FPC/COF 的軟板剝離強度測試依循 ASTM D903/ASTM D3807 系列標準規範手法；測試示意圖如下附圖所示。

Note 3 : The FPC/COF peeling strength test illustration is showed as below, and the test method follows the standard of ASTM

D903 / ASTM D3807.

訂單位 Department	文件名稱 Subject	文件編號 Document No.	
產品企劃部 Product Planning Dept.	產品規格書 Product Specifications	總頁數 Total Page	Page 7 / 15



2.2 可靠度規格 RELIABILITY SPECIFICATIONS

環境測試條件列表如下所示。

Environment test conditions are listed as follows.


項次 ITEMS	規格 SPECIFICATIONS
高溫高濕測試 Temperature Cycling	The product should be allowed to stand at $60\pm 2^{\circ}\text{C}$ with 90% RH for 240hrs un-load condition and started after leaving RA chamber 24 hrs and then can turn on the system .Water in TP surface need to be wipe down.
冷熱衝擊測試 Thermal Shock	The product should be allowed to stand at -40°C to $+85^{\circ}\text{C}$ for 30min/cycle with totally 50cycles and started after leaving RA chamber 24 hrs and then can turn on the system .Water in TP surface need to be wipe down.
高溫儲存測試 High Temp. Storage	The sample should be allowed to stand at $+85^{\circ}\text{C}$ for 240hrs un-load condition and started after leaving RA chamber 24 hrs and then can turn on the system .Water in TP surface need to be wipe down..
低溫儲存測試 Low Temp. Storage	The sample should be allowed to stand at -40°C for 240hrs un-load condition and started after leaving RA chamber 24 hrs and then can turn on the system .Water in TP surface need to be wipe down.

訂單位 Department	文件名稱 Subject	文件編號 Document No.	
產品企劃部 Product Planning Dept.	產品規格書 Product Specifications	總頁數 Total Page	Page 8 / 15

3. 外觀檢驗 APPEARANCE AND COSMETIC INSPECTION

3.1 檢驗環境參數 INSPECTION ENVIRONMENT CONDITIONS

- I. 觸控面板的目視檢查作業必須在至少無塵室等級為 10,000 的環境下執行。
The touch panel has to be inspected at a clean room of at least class 10,000.
- II. 觸控面板的目視檢查環境設定值必須被控制溫度在 15°C 到 25°C 以及濕度在 25%到 75%之間。
The visual inspection environment should be set at 15 to 25 degree C and 25% to 75% humidity.
- III. 觸控面板的外觀目視檢查之環境照度須設定在 800~1000Lux 的日光燈光源下。
The illumination of the appearance inspection should be 800~1000Lux with fluorescent reflection light source.
- IV. 觸控面板的目視檢查須在人眼裸視基礎下，並且觸控面板到人眼的目檢距離須至少超過 35 公分。
The visual inspection should be kept the distance 35cm or more between the touch panel and the raw eyes of inspectors.
- V. 觸控面板的裸眼目視檢查角度須以 45 度正負 10 度的角度作業。
The viewing angle should be 45±10 degree with an inspector' s raw eyes when visual inspection.
- VI. 外觀目視檢查時間建議為 25 秒正負 5 秒鐘的時間。
Visual inspection time is 25±5 second per one' s that we are recommended.
- VII. 髒污不良缺陷依據 25%灰度之點規進行判定。
The dirty defect should be judged with the 25% of contrast film in the point rule.
- VIII. 目視檢查示意圖如下附圖所示。
The visual inspection illustration is showed as below.



訂單位 Department	文件名稱 Subject	文件編號 Document No.	
產品企劃部 Product Planning Dept.	產品規格書 Product Specifications	總頁數 Total Page	Page 9 / 15

3.2 目視檢驗規範 COSMETIC SPECIFICATIONS

不良的分類共分為2種，分別是主要不良項目與次要不良項目；定義分別如下。

Defects are classified two types, one is major and the other is minor according to the defect specification, and they were definition as follows.

檢驗方法：依據 ANSI/ASQC C1.4-2003 一般檢驗規範等級二的抽樣標準比例。

Test method : According to ANSI/ASQC C1.4-2003. General Inspection Level II take a single time.

I. 主要不良項目 Major defect

任何可能導致有功能性失效或降低堪用率的不良原因；例如電性失效或外觀受損等。

Any defect may result in functional fail or reduce the usability such as electrical failure, deformation etc.

II. 次要不良項目 Minor defect

不會導致堪用率降低的不良原因；例如線性不良或點狀不良等等現象。

It doesn't reduce the usability such as line defect, dot defect etc.

III. 不良項目的抽樣判定等級標準依循如下：

The defects classify of AQL as following:



Major defect : AQL=0.65. Minor defect : AQL=2.5. Total defects : AQL=2.5.

※ 外觀不良定義與規範 ※

※ COSMETIC DEFECT DEFINITION AND SPECIFICATIONS ※

外觀不良定義 Cosmetic Defects Description		規格 Spec: W(寬度), L(長度), N(數量), D(直徑)=(W+L)/2, Distance (間距)	判定 Judge
線狀不良 Linear Defects 刮傷/擦痕/纖維/ 毛絮/雜質等 Scratch/ Scrub/ Fiber/Particle etc.	刮傷/擦痕 Scratch/Scrub	$W \leq 0.05\text{mm}$	Ignored
		$0.05\text{mm} < W \leq 0.1\text{mm}, L \leq 15\text{mm}$	Ignored
		$0.1\text{mm} < W \leq 0.2\text{mm}, L \leq 15\text{mm}, N \leq 5$	PASS
	纖維/毛絮/雜質 Fiber/Particle	$W > 0.2\text{mm}$ or $L > 15\text{mm}$	NG
		$W \leq 0.1\text{mm}, L \leq 10\text{mm}$	Ignored
		$0.1\text{mm} < W \leq 0.3\text{mm}, L \leq 10\text{mm}, N \leq 5, \text{Distance} \geq 5\text{mm}$	PASS
點狀不良 Dot Defects 氣泡/雜質/凹洞/ 白斑/黑斑等 Bubble/Particle/Dent/ White/Dark Dot etc.	可視區域 Active Area	$D \leq 0.2\text{mm}$	Ignored
		$0.2\text{mm} < D \leq 0.4\text{mm}, N \leq 5, \text{Distance} \geq 5\text{mm}$	PASS
		$D > 0.4\text{mm}$	NG
	印刷區域 Printing Area	$D \leq 0.2\text{mm}$	Ignored
		$0.2\text{mm} < D \leq 0.5\text{mm}, N \leq 5, \text{Distance} \geq 5\text{mm}$	PASS
		$D > 0.5\text{mm}$	NG
印刷不良 Printing Defects	針孔 Pin Hole	$D \leq 0.2\text{mm}$	Ignored
		$0.2\text{mm} < D \leq 0.3\text{mm}, N \leq 4, \text{Distance} \geq 2\text{mm}$	PASS
		$D > 0.3\text{mm}$	NG

訂單位 Department	文件名稱 Subject	文件編號 Document No.	
產品企劃部 Product Planning Dept.	產品規格書 Product Specifications	總頁數 Total Page	Page 10 / 15

	边缘漏光、锯齿 Light Leakage、Saw edge	黑框区域可接受:最高点至最低点距离 $\leq 0.2\text{mm}$ BM Area: Highest to lowest point by $\leq 0.2\text{mm}$	PASS
		Logo/icon 区域可接受:最高点至最低点距离 $\leq 0.1\text{mm}$ Logo/icon Area: Allowed from the highest to lowest point by $\leq 0.1\text{mm}$	PASS
	Ink Peeling 掉漆	在 VMI 站可补漆: Allow to repair with paint pen at VMI Cover 面按照规格判定; Sensor 面不允许存在台阶凹凸感。	
	色差 Discoloration	Logo/icon and BM 区域色差: 参考限度样品 Logo/icon and BM Area Discoloration: Follow the limit sample AG (AS&AR) 面色差: 参考限度样品 Follow the limit sample	
外观不良定义 Cosmetic Defects Description		规格 Spec: W(宽度), L(长度), N(数量) X:长, Y:宽, Z:高, T(玻璃厚度), Distance (间距)	判定 Judge
IR 孔/Icon/Logo 不良 IR Hole/Icon/Logo Defects	油墨不均 Uneven ink	黑色背景不可见或参考限度样品 Black background is not visible or follow limit sample	PASS
	白(黑)点 White (Dark) dot	$D \leq 0.1\text{mm}$	Ignored
		$0.1\text{mm} < D \leq 0.3\text{mm}$, $N \leq 5$, Distance $\geq 2\text{mm}$	PASS
	$D > 0.3\text{mm}$	NG	
其他不良 Others Defects	FPC 不良 FPC Defects	死折\破损 Crease\Broken	NG
	玻璃裂痕 Glass crack	不允许 Not Allowed	NG
	 角落破损 Corner chipping	Cover: $X \leq 0.1\text{mm}$, $Y \leq 0.1\text{mm}$, $Z \leq 0.1\text{mm}$ $X \leq 0.3\text{mm}$, $Y \leq 0.3\text{mm}$, $Z \leq T/2\text{mm}$, Per edge $N \leq 1$	Ignored PASS
		Sensor: $X \leq 3.0\text{mm}$, $Y \leq 3.0\text{mm}$, $Z \leq T/2\text{mm}$ Per edge $N \leq 3$, Distance $\geq 10\text{mm}$	PASS
	 边缘破损 Edge chipping	Cover: $X \leq 0.1\text{mm}$, $Y \leq 0.1\text{mm}$, $Z \leq 0.1\text{mm}$ $X \leq 0.3\text{mm}$, $Y \leq 0.3\text{mm}$, $Z \leq T/2\text{mm}$, Per edge $N \leq 3$, Distance $\geq 10\text{mm}$	Ignored PASS
		Sensor: $X \leq 3.0\text{mm}$, $Y \leq 3.0\text{mm}$, $Z \leq T/2\text{mm}$ Per edge $N \leq 3$, Distance $\geq 10\text{mm}$	PASS

訂單位 Department	文件名稱 Subject	文件編號 Document No.	
產品企劃部 Product Planning Dept.	產品規格書 Product Specifications	總頁數 Total Page	Page 11 / 15

4. 預防措施 PRECAUTIONS

項目 ITEM	說明 EXPLANATION
儲存 Storage	<ol style="list-style-type: none"> 觸控面板必須被儲存放置在一如規格書所建議的有從事環境溫度與濕度控制的區域內。 A touch panel should be stored under the environment temperature and humidity controlled as suggested. 不可將觸控面板直接曝曬在陽光下。 Do not store a touch panel in direct sunlight.
取放 Handling	<ol style="list-style-type: none"> 觸控面板要自包裝箱中取出時，請務必特別注意該包裝箱外的紅色箭頭符號是否朝上。 Unpack the carton with the printed red arrow pointing up. 無論任何時候都必須以拿取觸控面板本體為優先。 Hold a touch panel body instead of the FPC/COF all the time. 當 Sensor Glass 的保護膜被移除而準備從事組裝作業時，務必要避免 Sensor Glass 受到外在因素的污染。 Avoid that the surface of the sensor glass is polluted after removing the protect film when assembly.
清潔 Cleaning	<ol style="list-style-type: none"> 若要清潔觸控面板，請盡量避免使用諸如強酸或強鹼之類的任何化學溶劑。 Prevent using any kind of the chemical solvent, acidic or alkali solution when cleaning. 若要清潔觸控面板，我們建議使用中性的清潔劑或異丙醇和酒精等等。 Neutral detergent or isopropyl alcohol was suggested if the panel is cleaned.
組裝 Assembly	<ol style="list-style-type: none"> 觸控面板在組裝時，請不要過度施力導致玻璃表面發生諸如變形或扭曲等形變現象的發生。 Do not apply rough force such as bending or twisting to the touch panel during assembly. 對於 FPC 或 COF 的作業時，過度的拉力或繃緊作業是必須被禁止與避免的。 Excessive force or strain to the panel or FPC/COF is prohibited. 請在觸控面板與 TFT-LCD 面板的中間間隙處選用適合的雙面膠帶或是具有黏性的泡棉加以阻絕外在水份與污染源的干擾。 Past VHB tape or sponge with adhesive on the gap between a touch panel and a LCD module to segregate water and dust contamination.
操作 Operation	<ol style="list-style-type: none"> 觸控面板必須在穩定的環境狀況下被使用，環境狀態的突然急遽變化有可能會導致觸控面板的機能性失效的發生。 The panel must be operated in a steady environment, the abrupt change of the environment conditions may cause the malfunction of the panel.

訂單位 Department	文件名稱 Subject	文件編號 Document No.	
產品企劃部 Product Planning Dept.	產品規格書 Product Specifications	總頁數 Total Page	Page 12 / 15

項目 ITEM	說明 EXPLANATION
操作 Operation	<p>2. 為確保觸控面板的功能得以穩定有效的發揮呈現，請務必確認系統的接地迴路與電源供應器的接地迴路被正確的銜接與執行(與大地作共地的接地迴路是最佳的設計)。 In order to guarantee all functions of a touch panel stable, please make sure that system is grounded or a power adapter is connected correctly to ground loop (Connection to earth ground is suggested).</p> <p>3. 觸控面板在操作的過程中，請勿任意插拔觸控面板與系統端的界面連接器。 Do not pull the interface connector in or out while the touch panel is operating.</p> <p>4. 觸控面板在操作的過程中，請務必禁止與避免使用任何尖銳或硬質物體去敲擊碰觸。 Any sharp edged or hard objects are interdiction to hitting when touch panel operation.</p>
保證 Warranty	<p>1. 在正常的操作條件基礎下提供12個月的觸控面板模組(含 PCBA)保固服務。 Vendor will provide 12 months product (include PCBA) guarantee under normal operation conditions.</p>
其他 Others	<p>1. 本產品滿足 ROHS 的規範要求。 The product meets the specification requirement of the ROHS standard criteria.</p> <p>2. 假設觸控面板將被使用於諸如相對高溫，高濕度，高海拔或是長時間操作等較為嚴峻的操作條件時，中心的建議請事先諮詢產品應用工程人員並取得相關意見；否則關於產品的可靠度與功能是无法被有效的確保。 If the panel will be used in extreme conditions such as high temperature, high humidity, high altitude or long operation time etc., It is strongly recommended to contact Vendor for field application engineer's advice. Otherwise, Its reliability and function may not be guaranteed.</p> <p>3. 在觸控模組的單體下，請禁止與避免有任何高電壓或靜電衝擊等外在因素被加諸在模組上。 Avoid high voltage and/or static charge being applied to touch module.</p> <p>4. 保持觸控面板的潔淨度並避免任何具有黏性的物質粘附在觸控面板的表面上。 Keep the panel surface clean. Prevent any kind of adhesive applied on the surface.</p> <p>5. 本產品僅支援兩點觸控，超過兩指同時觸控時將無法動作。 It is support two fingers touch only and it would be malfunction when over two fingers touch together.</p> <p>6. 當操作觸控面板時，應避免有金屬或導電物質放置在面板上。 To avoid the metal or any kind of the electric conduction materials on the touch screen when you are handling.</p> <p>7. 觸控面板是藉由人體接觸操作，若有任何非導體被應用於該面板時，可能會出現觸控面板的機能失效。 Any kind of the non-electric conductor may cause the malfunction when that applied due to touch screen is sensing by human body.</p>

訂單位 Department	文件名稱 Subject	文件編號 Document No.	
產品企劃部 Product Planning Dept.	產品規格書 Product Specifications	總頁數 Total Page	Page 13 / 15

5. 標籤釋義 PRODUCT LABEL EXPLANATION

5.1 條碼定義 BARCODE DEFINITION

5.1.1 觸控面板編碼原則 Coding rule for touch screen level used

Serial ID: MT-A-B-CCC-DD-E-F-GG

CODE	MEANING	DESCRIPTION
MT	MT	Vendor internal use for account code
A	Numbers	Vendor internal use for material level classification
B	Letter	Vendor internal use for sub-category definition
CCC	Number	Vendor internal use for touch screen size definition
DD	Letter & Number	Vendor internal use for solution classification
E	Letter	Vendor internal use for interface definition
F	Letter	Vendor internal use for shielding definition of EMI and ESD
GG	Serial No.	Vendor internal use for manufacture sequence of product

Remark: Code "B" means "P" for Finished Goods (TP + C/B + FFC), "D" for Sub-Finished Goods (TP only), "C" for Control Board, etc...

Confidential

訂單位 Department	文件名稱 Subject	文件編號 Document No.	
產品企劃部 Product Planning Dept.	產品規格書 Product Specifications	總頁數 Total Page	Page 14 / 15

5.1.2 生產序號編碼原則 Coding rule for manufacturing serial used

Serial ID: A-B-C-D- E-FFFFF-G-H-II-JJJJ

CODE	MEANING	DESCRIPTION
A	Letter	Vendor internal use for production level classification
B	Letter	Vendor internal use for manufacture side classification
C	By year	Changed by 1~X
D	By month	Changed by 1~C
E	By day	Changed by 1~X
FFFFF	Letter	Vendor internal use for project code
G	Letter	Vendor internal use for project version No.
H	Letters	Vendor internal use for sub-category definition
II	Letters	Vendor internal use for WO No.
JJJJ	Serial No.	Vendor internal use for manufacture sequence of product

5.1.3 供應商集團內部管控編碼原則 Vendor internal control rule for group used.


TN ID: MS(MM)-A-B-CCC-DD- E-F-GG

CODE	MEANING	DESCRIPTION
MS/MM/ML	MS/MM/ML	Vendor group internal use control for production level classification
A	Number	Vendor internal use for material level classification
B	Letter	Vendor internal use for sub-category definition
CCC	Number	Vendor internal use for touch screen size definition
DD	Number & Letters	Vendor internal use for solution classification
E	Number	Vendor internal use for interface definition
F	Number	Vendor internal use for shielding definition of EMI and ESD
GG	Serial No.	Vendor internal use for manufacture sequence of product

訂單位 Department	文件名稱 Subject	文件編號 Document No.	
產品企劃部 Product Planning Dept.	產品規格書 Product Specifications	總頁數 Total Page	Page 15 / 15

6. 觸控面板圖面 TOUCH PANEL DRAWING

The information contained herein is the sole property of TPK Touch solutions INC. lent or reproduced with out an explicit written permission from the company.



For USB Connector	Pin Number	Pin Name
1	EGND	
2	VCC	
3	GND	
4	D+	
5	D-	

NAME	DATE	MATERIAL
DRAWN Carna Huang	17-07-14	
CHECKED Kawa Huang	17-07-14	

DATE	SCALE	UNIT
	1:1	mm

PROJECT NAME	PROJECT NO.	THROW ANGLE PROJECTION	VERSION
TPK Touch Solutions Inc.	HT9016035125		A

Front

Rear

Cover, t=1.1
TP, t=1.1

Acus 30224-0200-001

20.5±0.2

108.31±1.5

129.8

194.5±0.3 (CL A/A)

237.12±0.2 (CL V/V)

21.29±0.3

180±0.5

225.12±0.3 (TP D/D)

6±0.5

420.2

34.5±0.2

34.5±0.2

34.5±0.2

34.5±0.2

34.5±0.2

34.5±0.2

50.9±0.2

42±0.3

0.5±0.15

0.5±0.05

0.5±0.05

20.5±0.2

Rev	Revision note	Date	Signature	Checked
1.0	First release	17-07-14	Carna	Kawa